

PERISTALTIC PUMP



ENPD-100

Input Supply	230 VAC Single Phase
Type of motor	DC
No. of rollers	Two
Flow Rate	0.08 ml/min To 450 ml/min
Tube I.D.	0.8 mm To 7 mm
Wall thickness	1 To 2 mm
RPM of motor	1 to 160
Operational Duty	Continuous

ENPD-200

Input Supply	230 VAC Single Phase
Type of motor	DC
No. of rollers	Two
Flow Rate	4 ml/min To 1200 ml/min
Tube I.D.	0.8 mm To 10 mm
Wall thickness	1mm To 2 mm
RPM of motor	20 to 160
Operational Duty	Continuous

ENPD-300

Input Supply	230 VAC Single Phase
Type of motor	DC
No. of rollers	Two
Flow Rate	7 ml/min To 2100 ml/min
Tube I.D.	0.8 mm To 13 mm
Wall thickness	1mm To 2 mm
RPM of motor	20 to 160
Operational Duty	Continuous

ENPD-400

Input Supply	230 VAC Single Phase
Type of motor	DC
No. of rollers	Two
Flow Rate	50 ml/min To 3100 ml/min
Tube I.D.	3 mm To 15 mm
Wall thickness	1.4mm To 2.6 mm
RPM of motor	20 to 160
Operational Duty	Continuous

WORKING SIZE

FUNCTIONAL FEATURES	EXPRESS	VARIANTS OPTIMA	VICTOR
ON / OFF Control	✓	✓	✓
Digital Display	✓	✓	✓
Variable Speed (Flow Rate)	✓	✓	✓
Timer Mode		✓	✓
Sound		✓	✓
Volume Mode			✓
Calibration Mode			✓
Computer Connectivity			
Software Package			
# S.S. Construction (Optional)	✓	✓	✓
# Flame-Proof (Optional)	✓	✓	✓
# Flame-Proof with S.S. Cladding (Optional)	✓	✓	✓
Accessories			
# Foot Switch (Optional)	✓	✓	✓
# Remote Control (Optional)		✓	✓

External 4-20 mA, 0-5 V ,TTL and other control signal for ON/OFF, Speed and Direction control available on request.